
Nanoflyer

19971121 066

MITRE

DTIC QUALITY INSPECTED 3

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

Nanoflyer

Study Leader:
J. Katz

Contributors Include:
R. Garwin
W. Press

October 1997

JSR-97-115

Approved for public release; distribution unlimited.

JASON
The MITRE Corporation
1820 Dolley Madison Boulevard
McLean, Virginia 22102-3481
(703) 883-6997

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information estimated to average 1 hour per response, including the time for review instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE October 13, 1997		3. REPORT TYPE AND DATES COVERED
4. TITLE AND SUBTITLE Nanoflyer			5. FUNDING NUMBERS 13-988534-04	
6. AUTHOR(S) J. Katz, R. Garwin, W. Press				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The MITRE Corporation JASON Program Office 1820 Dolley Madison Blvd McLean, Virginia 22102			8. PERFORMING ORGANIZATION REPORT NUMBER JSR-97-115	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Advanced Research Projects Agency 3701 North Fairfax Drive Arlington, Va. 22203-1714			10. SPONSORING/MONITORING AGENCY REPORT NUMBER JSR-97-115	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE Distribution Statement A	
13. ABSTRACT (Maximum 200 words) A recent proposal to use electrostatic forces to lift and propel a small airborne vehicle is examined. We show here that although this is permitted by the laws of physics, it is very inefficient, and is limited to low areal loads by the requirement to avoid electric breakdown. Electrostatic propulsion offers no special advantages which might justify the price of its inefficiency.				
14. SUBJECT TERMS			15. NUMBER OF PAGES	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR	

ELECTROSTATIC FLIGHT

A recent proposal by Dædalus Research suggests using electrostatic forces to lift and propel a small airborne vehicle. We show here that although this is permitted by the laws of physics, it is very inefficient, and is limited to low areal loads by the requirement to avoid electric breakdown. Electrostatic propulsion offers no special advantages which might justify the price of its inefficiency.

In electrostatic propulsion, just as in propulsion by a rotating airfoil, it is not necessary to exert thrust directly downward in the manner of a helicopter. It may be possible to employ a wing to provide lift and to make the thrust horizontal, only overcoming the drag induced by flow over the wing. Just as for a conventional aircraft, this reduces the thrust required to maintain altitude, in comparison to that required by a helicopter, by the lift-to-drag ratio L/D of the vehicle. This is about 5 even for very small (cm-sized) wings, but may be less for the vehicle as a whole because of the necessity of moving a broad electrostatic propulsor broadside through the air.

The principle of electrostatic lift and propulsion is to fill a volume of air with a net negative charge density by introducing electrons from a field emitting cathode, and then to exert a force on this charged air by applying an electric field. The charged air fills the volume between two parallel flat electrodes, taken to be squares of side s separated by a distance b . We will make the approximation that this can be treated electrically as if $b \ll s$, neglecting fringing fields.

Electrons are assumed to be injected at the cathode by field emission at numerous sharp points, and then to attach to O_2 molecules, which have an

electron affinity of 0.44 eV, and are the only major component of air with a positive electron affinity. We assume all the electrons are bound in the form of O_2^- , which (using the Saha equation) is found to be a good approximation at room temperature, but which will not be correct at higher temperature. We also assume that no other ions are present; if other ions are created the efficiency will be less than even the low values we calculate.

The electric field between the electrodes accelerates the O_2^- towards the anode, and collisions transfer momentum to the neutral air molecules. The electrodes must be porous to admit a flow of neutral air through the cathode and to permit it to escape through the anode, at which the ions are neutralized. This flow of air provides the reaction force against which the electrostatic engine exerts its thrust, and is analogous to the downwash of a helicopter rotor or a propellor wake.

We first present a very simple rough estimate. Assume the charge density and electric field between the electrodes are uniform, which is correct in the limit in which the charge density is small (and the field imposed by the electrodes is large). Then the total charge contained between the electrodes is

$$Q = -n_i e s^2 b, \quad (1)$$

where n_i is the ion density and $-n_i e$ the net charge density. The magnitude of the thrust or force is

$$F = EQ, \quad (2)$$

where $E = V/b$ is the electric field produced by the electrodes and V is the potential drop.

The charge Q produces an additional electric field which tends to push the ions and air out from between the electrodes, keeping the ions from reaching the anode by the most direct path and reducing the reaction force imparted to the air. This is undesirable, because it reduces the net charge

Q on which the imposed field acts, increases the frictional losses as ions are pushed laterally through the neutral air, and reduces the net field acting on the net charge. We can approximate this self-field

$$E_s \sim \frac{Q}{(s/2)^2} \text{ for } b \leq s \quad (3)$$

($b > s$ is an inefficient electrode geometry because the fringing fields are dominant).

In order for the efficiency to approach its maximum value we must have

$$E_s < E. \quad (4)$$

Then

$$Q < \frac{F^{1/2}s}{2}. \quad (5)$$

In order to minimize E (which will turn out to be uncomfortably large) we maximize Q by taking the inequality (5) to be an equality. Then

$$E = 2 \left(\frac{F}{s^2} \right)^{1/2} \quad (6)$$

and

$$V = 2b \left(\frac{F}{s^2} \right)^{1/2}. \quad (7)$$

There are two concerns: the power which must be expended to supply the thrust F and the magnitude of the potential. The power expended is largely that dissipated resistively at a rate jE per unit volume, where j is the current density. The ratio of power to thrust

$$\frac{P}{F} = \frac{jEs^2b}{F} = \frac{n_i e Es^2 b v_{dr}}{F} = \frac{QE v_{dr}}{F} = v_{dr}, \quad (8)$$

where v_{dr} the ion-neutral drift velocity, given by

$$v_{dr} = kE. \quad (9)$$

The mobility of O_2^- in air $k = 4.4 \text{ cm}^2/(\text{Volt s}) = 1.3 \times 10^3 \text{ cgs}$. Hence

$$\frac{P}{F} = 2k \left(\frac{F}{s^2} \right)^{1/2}. \quad (10)$$

For plausible values of $F = 10^3$ dyne and $s = 1$ cm, $P/F = 8 \times 10^4$ cm/s. We have ignored inefficiencies resulting from the significant value of E_s , viscous drag in air flow through the porous electrodes, *etc.*, which may be significant.

This value of P/F should be compared to the value found for more conventional propulsion by rotating airfoils, which is $\approx [F/(\rho_{air}s^2)]^{1/2} \approx 900$ cm/s. Electrostatic propulsion demands nearly 100 times as much power, a ratio which is independent of the areal loading F/s^2 . The reason for this inefficiency is the large power dissipated in friction between the ions and the neutral air, whose relative drift velocity is v_{dr} .

The required electric fields are large. For the previous parameters $E \approx 20,000$ Volts/cm. This is uncomfortably close to the breakdown field of 30,000 Volts/cm for air. In the neighborhood of the field-emitting points the field is substantially larger, and at least corona discharge may occur.

In the thin capacitor limit ($b \ll s$) an exact calculation, allowing for the effect of the self-field of the space charge, is straightforward. Poisson's equation for the electrostatic potential is

$$\nabla^2 \phi = \frac{d^2 \phi}{dz^2} = -4\pi n_i e, \quad (11)$$

where z measures the distance from the cathode. The conservation of charge implies that the current density j is constant, and j is related to the electric field by the ion mobility:

$$j = E(z)n_i(z)ek \quad (12)$$

Eliminating $n_i(z)e$ gives

$$\frac{4\pi j}{kE(z)} = -\frac{d^2 \phi}{dz^2} = \frac{dE(z)}{dz}. \quad (13)$$

Upon integration

$$E(z) = \left[\frac{8\pi j}{k}(z - z_0) \right]^{1/2}. \quad (14)$$

The constant of integration z_0 depends on the charge density. The maximum possible charge (and hence the smallest electric field for a given surface loading F/s^2) is found if $z_0 = 0$, so that the field drops to 0 at the cathode (the charge density $-n_i(z)e$ becomes infinite there, by Equation 12). The surface loading is found from the difference in electric stresses at the two electrodes:

$$\frac{F}{s^2} = \frac{E^2(b) - E^2(0)}{8\pi} = \frac{jb}{k}. \quad (15)$$

The power dissipated is

$$\frac{P}{s^2} = \int jE dz = j \int E dz = jV. \quad (16)$$

The ratio of power to surface load is

$$\frac{P}{F} = \frac{Vk}{b} = \frac{2}{3}kE(b). \quad (17)$$

The field $E(b)$ is 2.5 times the rough estimate of Equation 6; requiring $E(b) < 30,000$ Volts/cm to avoid breakdown limits the surface loading to 400 dyne/cm². Equation (14) shows that $E(b) = 3V/(2b)$; that is; the ionic space charge increases the field at the anode by 50% compared to a uniform field with the same potential. At this surface loading the ratio of power to thrust is 9×10^4 cm/s, close to the rough estimate of Equation 10. The ratio P/F for a rotating airfoil with the same surface loading is ≈ 550 cm/s. Electrostatic propulsion demands about 150 times more power than a rotating airfoil, a ratio more pessimistic than the rough estimate, but again independent of the areal loading.

Another way of looking at the inefficiency of electrostatic propulsion is to estimate the endurance of such an aircraft. This depends on the power supply, which we will take to be a battery with the highest estimated specific energy of any battery, $\mathcal{E} = 400$ Wh/kg $= 1.44 \times 10^{10}$ erg/gm for lithium thionyl chloride. Fuel cells may provide a few times higher specific energy, but are not available off the shelf. Hydrocarbon fuels have even higher high energy content (roughly an order of magnitude greater than that of the best

batteries), but micro-scale heat engines and generators do not exist, and may have low efficiency if they are built. Taking a fraction f_b of the vehicle's mass M as battery and equating the energy available to the power expended in an endurance time t yields

$$f_b \mathcal{E} M = \frac{g M (P/F) t}{L/D}, \quad (18)$$

where $L/D = 1$ if the thrust is exerted directly downward, as in a helicopter. Substituting $f_b = 0.5$, $L/D = 1$ and taking the previously estimated $P/F = 9 \times 10^4$ cm/sec yields

$$t = \frac{f_b \mathcal{E} (L/D)}{g (P/F)} = 85 \text{ sec.} \quad (19)$$

The numerical value depends on a number of parameters whose values can only be estimated (for example, it is not possible to draw the energy of a battery nearly as fast as required). It is still apparent that the endurance time is hundreds of times shorter than that of more conventionally powered aircraft, and is too short to be useful.

DISTRIBUTION LIST

Director of Space and SDI Programs
SAF/AQSC
1060 Air Force Pentagon
Washington, DC 20330-1060

CMDR & Program Executive Officer
U S Army/CSSD-ZA
Strategic Defense Command
PO Box 15280
Arlington, VA 22215-0150

Superintendent
Code 1424
Attn Documents Librarian
Naval Postgraduate School
Monterey, CA 93943

Director
Technology Directorate
Office of Naval Research
Room 407
800 N. Quincy Street
Arlington, VA 20305-1000

DTIC [2]
8725 John Jay Kingman Road
Suite 0944
Fort Belvoir, VA 22060-6218

Dr Albert Brandenstein
Chief Scientist
Office of Nat'l Drug Control Policy
Executive Office of the President
Washington, DC 20500

Dr H Lee Buchanan, I I I
Director
DARPA/DSO
3701 North Fairfax Drive
Arlington, VA 22203-1714

Dr Collier
Chief Scientist
U S Army Strategic Defense Command
PO Box 15280
Arlington, VA 22215-0280

D A R P A Library
3701 North Fairfax Drive
Arlington, VA 22209-2308

Dr Victor Demarines, Jr.
President and Chief Exec Officer
The MITRE Corporation
A210
202 Burlington Road
Bedford, MA 01730-1420

Mr Dan Flynn [5]
OSWR
Washington, DC 20505

Dr Paris Genalis
Deputy Director
OUSD(A&T)/S&TS/NW
The Pentagon, Room 3D1048
Washington, DC 20301

Dr Lawrence K. Gershwin
NIC/NIO/S&T
7E47, OHB
Washington, DC 20505

Dr Robert G Henderson
Director
JASON Program Office
The MITRE Corporation
1820 Dolley Madison Blvd
Mailstop W553
McLean, VA 22102

DISTRIBUTION LIST

Dr William E Howard III [2]
Director of Advanced Concepts &
Systems Design
The Pentagon Room 3E480
Washington, DC 20301-0103

J A S O N Library [5]
The MITRE Corporation
Mail Stop W002
1820 Dolley Madison Blvd
McLean, VA 22102

Dr Anita Jones
Department of Defense
DOD, DDR&E
The Pentagon, Room 3E1014
Washington, DC 20301

Mr. O' Dean P. Judd
Los Alamos National Laboratory
Mailstop F650
Los Alamos, NM 87545

Dr Bobby R Junker
Office of Naval Research
Code 111
800 North Quincy Street
Arlington, VA 22217

Dr Ken Kress
Office of Research and Development
809 Ames Building
Washington, DC 20505

Lt Gen, Howard W. Leaf, (Retired)
Director, Test and Evaluation
HQ USAF/TE
1650 Air Force Pentagon
Washington, DC 20330-1650

Mr. Larry Lynn
Director
DARPA/DIRO
3701 North Fairfax Drive
Arlington, VA 22203-1714

Dr. John Lyons
Director of Corporate Laboratory
US Army Laboratory Command
2800 Powder Mill Road
Adelphi, MD 20783-1145

Col Ed Mahen
DARPA/DIRO
3701 North Fairfax Drive
Arlington, VA 22203-1714

Dr. Arthur Manfredi
OSWR
Washington, DC 20505

Mr James J Mattice
Deputy Asst Secretary
(Research & Engineering)
SAF/AQ
Pentagon, Room 4D-977
Washington, DC 20330-1000

Dr George Mayer
Office of Director of Defense
Reserach and Engineering
Pentagon, Room 3D375
Washington, DC 20301-3030

Dr Bill Murphy
ORD
Washington, DC 20505

Dr Julian C Nall
Institute for Defense Analyses
1801 North Beauregard Street
Alexandria, VA 22311

DISTRIBUTION LIST

Dr Ari Patrinos [5]
Director
Environmental Sciences Division
ER74/GTN
US Department of Energy
Washington, DC 20585

Dr Bruce Pierce
USD(A)D S
The Pentagon, Room 3D136
Washington, DC 20301-3090

Mr John Rausch [2]
Division Head 06 Department
NAVOPINTCEN
4301 Suitland Road
Washington, DC 20390

Records Resource
The MITRE Corporation
Mailstop W115
1820 Dolley Madison Blvd
McLean, VA 22102

Dr Victor H Reis [5]
US Department of Energy
DP-1, Room 4A019
1000 Independence Ave, SW
Washington, DC 20585

Dr Fred E Saalfeld
Director
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217-5000

Dr Dan Schuresko
O/DDS&T
Washington, DC 20505

Dr John Schuster
Technical Director of Submarine
and SSBN Security Program
Department of the Navy OP-02T
The Pentagon Room 4D534
Washington, DC 20350-2000

Dr Michael A Stroschio
US Army Research Office
P. O. Box 12211
Research Triangle NC27709-2211

Ambassador James Sweeney
Chief Science Advisor
USACDA
320 21st Street NW
Washington, DC 20451

Dr George W Ullrich [3]
Deputy Director
Defense Nuclear Agency
6801 Telegraph Road
Alexandria, VA 22310

Dr. David Whelan
Director
DARPA/TTO
3701 North Fairfax Drive
Arlington, VA 22203-1714

Dr Edward C Whitman
Dep Assistant Secretary of the Navy
C3I Electronic Warfare & Space
Department of the Navy
The Pentagon 4D745
Washington, DC 20350-5000